



## DIBIPACK 4255 EV

### THE MOST UP-TO-DATE TECHNOLOGY IN HEAT-SHRINKING

Simplified heat-shrinking wrappers with advanced control and management of cycle, designed to guarantee high performances together with ease of use and maintenance.

- Working Cycle electronically controlled by a microprocessor
- Automatic adjustment of sealing-time: the machine adjusts the sealing-time automatically according to the packaging speed
- It is possible to memorize 8 different working programs
- Energy-saving function: the machine goes in "stand-by" if it does not work for a recordable period
- Possibility to start shrinking when sealing is completed
- Hold-down solenoid: the hood remains closed up to the end of shrinking
- Starting control with proximity
- Hood may be released after fan stopping to avoid the escape of hot air at the end of the cycle
- Unit counter
- Reopening system through gas spring
- Scrap-rewind on request
- The machine works with PVC, polyolefin hot thermo-sealing and also shrinkable films.



Machine manufactured according to CE safety rules.

SPECIFICATIONS	DIBIPACK 4255 EV
Power supply	230 V- 1 Ph
Maximum power required	3 KW
Overall machine dimensions L x W	1270 x 780 mm
Working plate height (on stand)	920 mm
Machine weight	87 kg
Sealing area W x L	420 x 550 mm
Maximum product height	200 mm
Impulse sealing system	Bottom blade
Maximum roll dimensions DIA x W	250 x 600 mm
Output	4 - 6 pcs/min

**Note: Technical data subject to variations without prior notice.  
Output depends on the operator and the type of article to be wrapped.**